

CODE DIVISION MULTIPLE ACCESS MODEM INTERFACE

This application claims priority from U.S. Provisional Application No. 60/192,230, filed on March 27, 2000.

BACKGROUND

5 The present invention generally relates to wireless communication networks. In particular, the invention relates to modem interfaces used in wireless communication networks.

10 Modem interfaces as used in wireless communication networks, such as code division multiple access (CDMA) wireless networks, are commonly used to transfer data between wired components of the network and a wireless air interface 38 of the network. Figure 1 illustrates a simplified wireless communication network. A user terminal 20 is connected to a local exchange 22. The user terminal 20 transmits data over the local exchange 22 through a radio distribution unit (RDU) 24.

15 The data sent through the RDU 24 is received by a modem 28 in a radio carrier station (RCS) 26 prior to transmission over the air interface 38. The modem interface 34 takes the data that was transferred over the local exchange 22 and RDU 24 and converts it into a format compatible with the transmit circuitry 36 of the modem 28. The transmit circuitry 36 converts the data into a format suitable for transmission over the wireless air interface 38. The data is subsequently transmitted over the air interface 38 by the base station 30 and received by an antenna 42 at a radio network terminal (RNT) 40. The received signals are processed by the receive circuitry 32 of the RNT's modem 28. The processed signals are sent to a modem interface 34 which converts the signals into a format

20

to be sent to a second user terminal 46.

Sub G1/ Conversely, data to be sent by the second user terminal 46 is sent to the modem interface 34 of the RNT 40. The data is processed to be in a format suitable for the transmit circuitry 32 of the modem 28. The transmit circuitry 36 converts the processed data into a format suitable for transfer over the air interface 38. The data is subsequently transmitted over the air interface 38 using an antenna 42 and received by the base station 30. The received data is processed by the receive circuitry 34 of the base station's modem 28. The processed data is further processed by the modem interface 34 to be in a format suitable for transmission through the RDU 24 and local exchange 22. The data is subsequently transferred through the RDU 24 and local exchange 22 to the user terminal 20.

In the past, wireless communication networks were used primarily to transfer voice signals. However, the demand for wireless transmission of data is ever increasing. In particular, the demand for transmitting high data rates, such as those required for integrated services digital networks (ISDNs), over wireless networks is ever increasing. Accordingly, it is desirable to have a modem interface capable of handling high data rates.

SUMMARY

Sub G2/ A modem interface transfers data between the high data rate interface and a wireless interface. The wireless interface has a plurality of parallel data highways. Each data highway has frames with time slots for transferring data. The plurality of highways outputs data to the high data rate interface and the wireless interface in selected time slots. At least one of the data highways has an input configured to receive data from the high data rate interface in selected time slots. At least one of the data highways has an input configured to receive data from the wireless interface in selected time slots. A processor controls the transfer of data between the plurality of highways.

BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 illustrates a wireless communication network.

Figure 2 is a modem interface.

Figure 3 illustrates a wireless communication network carrying integrated services digital network (ISDN) signals.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Sub Q3 Figure 2 illustrates a modem interface 56. As shown in Figure 3, the modem interface 56 is used to transfer data between a high data rate terminal, such as an integrated services digital network (ISDN) terminal 60, and a wireless air interface 38. The modem interface 56 may be located on the RNT side of the wireless air interface as being a component of the RNT 40. Similarly the modem interface 56 may be used on the base station side of the air interface 56, such as within the RCS 26. The modem interface 56 is preferably located at both the RNT 40 and RCS 26.

Sub Q4 If used on the RNT side, the modem interface 56 receives data from the ISDN terminal 60 over an ISDN oriented modular-2 highway (IOM-2 highway) 62. Conversely, the modem interface 56 also sends data to the ISDN terminal 60 over the IOM-2 highway 62. If used on the base station side, the modem interface 56 transfers data over a pulse code modulation (PCM) highway 62, preferably at an E1 data rate.

Data transmitted to and from the ISDN terminal 60 is sent over eight (8) channels, each in a 2B + D format. Data is sent over each of two (2) B channels. Each B channel has a data rate of 64 kilobits per second (Kbs). Data is also sent over a D channel having a data rate of 16 Kbs. The data sent over the D channel is control data, and is high-level data link controlling (HDLC) encoded. Additionally, each channel has a control information (CI) channel, an MR channel and an MX channel. The CI channel carries line information at a

I-2-116.1US

32 Kbs data rate. The MR and MX channels are used for handshake for the CI channel. Each has a data rate of 8 Kbs.

HDLC encoding converts data into frames. Each frame has six (6) fields. Two of these fields are flag fields which are used for synchronization. They indicate the start and end of a frame. An address field identifies the destination for that frame. A control field identifies the function and purpose of the frame. A data field contains the data for transmission. A circular redundancy code (CRC) field is used for error detection and correction.

A PCM/IOM interface 64 transfers data between the IOM-2 or PCM highway 62 and the external PCM highway 66. Preferably, the external PCM highway 66 has a data rate of 2 megabits per second. If used on the RNT side, the PCM/IOM interface 64 converts the PCM data into IOM-2 data and vice versa. If used on the base station side, the PCM/IOM interface 64 merely passes through the PCM data in both directions.

To transfer data between the various components of the modem interface 56, a multiple data highway structure is used, such as three (3) PCM highways I-III 68₁-68₃ shown in Figure 2. Each PCM highway 68₁-68₃ uses repeating frames having multiple time slots. A preferred frame would have sixteen (16) time slots numbered from zero to fifteen (TS0-TS15). Each preferred time slot is sixteen (16) bits in length. Each PCM highway 68₁-68₃ has an associated maximum data rate, such as 2 megabits per second. For three PCM highways 68₁-68₃, each having a 2 megabit per second data rate, the combined data rate is 6 megabits per second. Accordingly, multiple PCM highways 68₁-68₃ with lower data rates, such as 2 megabits per second, can be used to effectively transfer data at a much higher data rate, such as 4, 6 or 8 megabits per second. The multiple PCM highways 68₁-68₃ allow the modem interface 56 to utilize PCM highways 68₁-68₃ with a standard data rate, such as 2 megabits per second, and effectively transfer data at a much higher rate. Using a standard

data rate PCM highway 68_1 - 68_3 simplifies the structure of the highways 68_1 - 68_3 . Additionally, since the multiple highways 68_1 - 68_3 can be selected to have the same data rate as the PCM highway 66, only a single clock domain is required for the highways 66, 68_1 - 68_3 . As a result, power consumption and noise are reduced and testability is improved.

5 Clock routing is also simplified by using only a single clock domain.

One possible assignment using three (3) PCM highways 68_1 - 68_3 , each having 16 time slots (TS0-TS15) is as follows. For PCM highway I 68_1 , TS0-TS15 are all assigned to transferring data to and from the external PCM highway 66 and the PCM highway I 68_1 . A group of read devices 70_1 - 70_n read data from the corresponding time slots on PCM highway I 68_1 and a corresponding group of write devices 72_1 - 72_n write that read data onto the IOM PCM highway 66. Conversely, a group of read devices 74_1 - 74_n read data from the IOM PCM highway 66 and a corresponding group of write devices 76_1 - 76_n write that data onto the corresponding slots on PCM highway I 68_1 .

Each write device is fixed to a predetermined time slot. Each read device can read data from any time slot on any highway 68_1 - 68_3 . The advanced instruction set computer (ARM) processor 88 controls which time slot that each read device reads.

The external PCM highway 66 preferably uses repeating frames of 125 microsecond duration. The read devices 74_1 - 74_n can read data starting at any bit in the frame and at a variety of data rates. The starting bit is controlled by a PCM slot parameter and the data rate is controlled by a PCM rate parameter. The ARM processor 88 determines the PCM slot and rate parameters.

Sub 6.5 PCM highway II 68_2 is used to transfer data to and from the digital signal processor (DSP) 78 using TS0-TS7. One such DSP 78 is a 54x family processor, preferably a TMS320C54x processor. The DSP 78 may perform functions such as speech, video compression or encryption. Data is read from the PCM highway II 68_2 using a group of read

devices 80₁-80_n. The read data is buffered by a group of buffers 84₁-84_n and then sent to the DSP 78. Data sent from the DSP 78 is buffered by a group of buffers 86₁ and then written into the corresponding time slots of the PCM highway II 68₂ using a group of write devices 82₁-82_n. TS8 - TS15 of the PCM highway II 68₂ are used to interface with telephone interface components.

The ARM processor 88 typically has an associated external flash memory. The ARM processor 88 controls various aspects of the modem 48. Data is read from TS8-TS15 using a group of read devices 90₁-90_n. The read data is buffered by a group of buffers 92₁-92_n and sent to an IOM interrupt device 98 and the ARM processor 88. The output from the IOM interrupt device 98 is also input to the ARM processor 88. The IOM interrupt device 98 determines whether the C/I channel data has changed from frame to frame and will notify the ARM processor 88 when a change is detected. Conversely, the ARM processor 88 sends data to a group of buffers 94₁-94_n. Write devices 96₁-96_n take the buffered data and write it to the corresponding time slots of the PCM highway II 68₂.

An ARM port interface (API) 140 is a shared memory interface between the ARM processor 88 and the DSP 78 and transfers control signals between the ARM 88 and DSP 78. The API 140 preferably has a two kiloword block of memory. The DSP 78 is slaved to the ARM 88. The ARM 88 controls the interrupts and resets of the DSP 78. Conversely, the DSP 78 can interrupt the ARM processor 88.

TS0-TS8 of PCM highway III 68₃ are used for HDLC processing. Data in TS0-TS8 are read by the HDLC reading devices 108₁-108_n. Data from TS0 - TS2 is processed by an HDLC multiplexer (HMUX) 112 which sends processed data to an input/output (I/O) device 116 and an HDLC I controller 114₁. Data is also sent from the I/O devices 116 and HDLC I controller 114₁ to the HMUX 112. The data processed by the HMUX 112 from the I/O device 116 and HDLC I device 114₁ is written to TS0-TS2 of PCM highway III 68₃ using

a HDLC write device 110₁. Data in TS3-TS8 is transferred to and from the other two HDLC controllers (HDLC II 110₂, TS3-TS5, and HDLC III 110₃, TS6-TS8). The data in the corresponding slots is read by HDLC read devices 108₂, 108₃ prior to being sent to the corresponding HDLC controller 114₂, 114₃. Data from the HDLC II 114₂ and HDLC III 114₃ controllers is sent to the HDLC write devices 110₂, 110₃ and written onto the corresponding slots of PCM highway III 68₃. Data from each of the three HDLC controllers (HDLC I 114₁, HDLC II 114₂ and HDLC III 114₃) is transferred back and forth to the ARM processor 88. The HDLC controllers 114₁-114₃ are used to communicate with the ARM processor 88 or the traffic channels.

The HDLC controllers (HDLC I 114₁, HDLC II 114₂ and HDLC III 114₃) are used to encode the D channel for transfer over the air interface 38 and decode the D channel after transmission over the air interface 38. As previously mentioned, the D channel is HDLC encoded. To assure that the integrity of the HDLC encoding is preserved after transmission over the air interface 38, the D channel is again HDLC encoded prior to transmission across the wireless air interface 38 by the HDLC controllers 114₁-114₃. Accordingly, the control data is double HDLC encoded. This double encoding allows for error correction over the air interface 38 and for the integrity of the originally HDLC encoded D channel to be maintained.

Conversely, the HDLC controllers 114₁-114₃ also decode a double HDLC encoded D channel received over the wireless interface 38. The double HDLC encoded D channel is stripped of the second HDLC encoding by the HDLC controllers 114₁-114₃. The CRC field data is used to correct any errors that occurred during the wireless transfer. Accordingly, the original D channel is recovered. Preferably, each HDLC controller 114₁-114₃ processes data at 384 Kbs and require 3 128 Kbs time slots.

TS9-11 of PCM highway III 68₃ are used to transfer data to and from the ARM

processor 88. A group of read devices 100_1-100_n read data from the corresponding slots of PCM highway III 68_3 . The read data is buffered by a group of buffers 102_1-102_n and is sent to the ARM processor 88. The ARM processor 88 sends data to a group of buffers 94_1-94_n . The buffered data is written by corresponding write devices onto PCM highway III 68_3 .

5 If the modem interface 56 is used at a base station, the frame synchronization and clock are input to the interface 56. If used in a RNT 40, the frame synchronization and clock are generated by the RNT 40, such as on an application specific integrated circuit (ASIC) containing the interface 56.

TS12-TS15 of PCM highway III 68_3 are used to carry data received over the air interface 38 and to be sent over the air interface 38. Data received over the air interface 38 is preferably modulated using quadrature phase shift keying (QPSK), although other modulation schemes may be used. Prior to being input to the modem interface 56, the received data is decoded using a double speed quadrature viterbi decoder, although other decoding schemes may be used. The viterbi decoder preferably decodes four received traffic channels (QVD_TR0 - QVD_TR3). Preferably, the data rates supported are 8, 16, 32, 64, 128 Kbs. The ARM processor 88 controls the read assignments to the multiple PCM highways 68_1-68_3 effectively controlling data routing and data rate.

Data to be sent over the air interface 38 is preferably convolutionally encoded, spread and transmitted using QPSK modulation, although other wireless transmission schemes may be used. The data is preferably sent over four traffic channels (TR0-TR3).

20 Data to be sent over the wireless interface 38 is read by a group of read devices 118_1-118_4 . One read device 118_1-118_4 is used per traffic channel, TR0-TR3. Another set of read devices is used for encryption of each channels data 120_1-120_4 . The output of one 120_1-120_4 of each channel's encryption read devices is input into a parallel to serial converter 122_1-122_4 . The serial output of that converter 124_1-124_4 is fed into another parallel to serial

converter 124₁-124₄ which also receives the output of the other one of that channel's read devices 118₁-118₄. The two serial outputs are modulo-2 added on a bit basis to encrypt the data. Each channel's encrypted serial output is typically sent to a corresponding convolutional encoder, spreader and modulator for transfer over the wireless interface 38.

5 Each parallel to serial converter 118₁-118₄ is programmed to produce data at a desired bit rate.

sub
Q10
10
5
Encrypted data received from traffic channels, such as QVD_TR0-QVD_TR3, is input to a group of serial to parallel converters 126₁-126₄. Each channel's serial to parallel converter 126₁-126₄ combines that traffic channel's data with an output of a parallel to serial converter 128₁-128₄ to decrypt the traffic data. The decryption data from each parallel to serial converter 128₁-128₄ originates from data read from TS12-TS15 by corresponding read devices 138₁-138₄. The read data is converted from parallel to serial format by the parallel to serial converters 128₁-128₄. The serial outputs of the serial to parallel converters 126₁-126₄ are inputted to a group of write devices 132₁-132₄ which write the serial output to a group of multiplexers 130₁-130₄. The multiplexed data is sent to TS12-TS15 of the PCM highway III 68₃. For testing, the DSP 78 outputs a signal to a group of buffers 136₁-136₄. The output of the buffers 136₁-136₄ is also input to the multiplexers 130₁-130₄.

*

*